

75 Ohm P3® Trunk and Distribution Cable, unjacketed



Product Classification

Product Type	Coaxial hardline cable
Product Brand	P3®
Warranty	One year

General Specifications

Cable Type	625 Series
Construction Type	Swaged
Jacket Color	Unjacketed
Short Description	P3 625 CA

Dimensions

Cable Length	731.52 m 2400 ft
Diameter Over Center Conductor, nominal	3.48 mm 0.137 in
Diameter Over Dielectric, nominal	14.351 mm 0.565 in
Diameter Over Outer Conductor, nominal	15.875 mm 0.625 in
Outer Conductor Thickness, nominal	0.762 mm 0.03 in

Electrical Specifications

Capacitance	50.197 pF/m 15.3 pF/ft
Capacitance Tolerance	±1.0 pF/ft
Characteristic Impedance	75 ohm
Characteristic Impedance Tolerance	±2 ohm
dc Resistance Note	Nominal values based on a standard condition of 20 °C (68 °F)
dc Resistance, Inner Conductor, nominal	2.756 ohms/km 0.84 ohms/kft

5208002 | P3® 625 CA

dc Resistance, Loop, nominal	3.609 ohms/km 1.1 ohms/kft
dc Resistance, Outer Conductor, nominal	0.853 ohms/km 0.26 ohms/kft
Nominal Velocity of Propagation (NVP)	87 %
Operating Frequency Band	5–3000 MHz
Structural Return Loss	24 dB @ 1003–1218 MHz 24 dB @ 1219–1794 MHz 30 dB @ 5–1002 MHz
Structural Return Loss, Grade N	≥24 dB @ 1003–1218 MHz ≥24 dB @ 1219–1794 MHz ≥30 dB @ 5–1002 MHz

Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
5.0	0.43	0.13
55.0	1.48	0.45
85.0	1.84	0.56
204.0	2.92	0.89
211.0	3.02	0.92
250.0	3.28	1
300.0	3.54	1.08
350.0	3.87	1.18
400.0	4.17	1.27
450.0	4.43	1.35
500.0	4.69	1.43
550.0	4.92	1.5
600.0	5.18	1.58
750.0	5.84	1.78
865.0	6.33	1.93
1002.0	6.92	2.11
1218.0	7.62	2.32
1500.0	8.74	2.66
1794.0	9.7	2.96
1800.0	9.72	2.96
2000.0	10.34	3.15
2200.0	10.95	3.34
2500.0	11.81	3.6
2700.0	12.37	3.77
3000.0	13.19	4.02

Material Specifications

Center Conductor Material	Copper-clad aluminum
Dielectric Material	Foam PE
Jacket Material	Unjacketed
Outer Conductor Material	Aluminum

Mechanical Specifications

Pulling Tension, maximum	215.456 kg 475 lb
---------------------------------	---------------------

Environmental Specifications

Environmental Space	Aerial
----------------------------	--------

Packaging and Weights

Packaging Type	Reel
Weight, gross	235.13 kg/km 158 lb/kft

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

