MC-DPM2M-6-96



Monopole Co-location Dual Pipe Mount Kit, 12 in to 50 in OD, 4 ft 9 in face, includes pipes

Product Classification

Product TypeCo-location dual pipe mount kit

General Specifications

Mounting Monopole, 304.8–1270 mm (12–50 in) OD

Pipe, quantity 6
Sectors, quantity 3

Dimensions

Height 2,438.4 mm | 96 in **Face Width** 1.463 m | 4.8 ft Width 1,447.8 mm | 57 in Length 355.6 mm | 14 in Pipe Length 2,438.4 mm | 96 in Mounting Diameter, maximum 1270 mm | 50 in **Mounting Diameter, minimum** 304.8 mm | 12 in **Pipe Outer Diameter** 60.96 mm | 2.4 in Stand-off Distance 355.6 mm | 14 in

Mounting Circumference, maximum3,990.34 mm | 157.1 inMounting Circumference, minimum1,196.34 mm | 47.1 in

Material Specifications

Material Type Hot dip galvanized steel

Mechanical Specifications

Wind Rating 120 mph (BWS) at 150 ft AGL | 140 mph (3-second gust) at 150 ft AGL using Exposure D

Page 1 of 2

MC-DPM2M-6-96

per FBC

Wind Rating Criteria Two 72 in x 8 in panel antennas per sector

Wind Rating Test Method TIA/EIA-222-G

Packaging and Weights

Included Dual pipe frames | Pipe mounts | Ring mount

Packaging quantity 1

Weight, net 326.587 kg | 720 lb

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

* Footnotes

Wind Rating BWS—Base Wind Speed; FBC—Florida Building Code

