


1671495-2



High-Density Front-Loading Cable Manager, 2U

- Offers bend radius and mechanical protection
- Suitable for Twisted Pair and Fiber Optic patch cords
- Rubber entry/exit retainers ensure cable captivity preventing accidental disturbance of patch cords

Product Classification

| | |
|-------------------------------|---|
| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |
| Portfolio | CommScope® |
| Product Type | Cable management hardware |
| Minimum Order Quantity | 8 |
| Ordering Note | Sold per piece with an MOQ of 8 pieces |

General Specifications

| | |
|-------------------|-------|
| Color | Black |
| Rack Units | 2 |

Dimensions

| | |
|---------------|----------------------|
| Height | 88.9 mm 3.5 in |
| Width | 63.5 mm 2.5 in |
| Depth | 150.114 mm 5.91 in |

Material Specifications

| | |
|----------------------|-----------------------------|
| Finish | Smooth |
| Material Type | Galvanized steel PA TPE |

Environmental Specifications

| | |
|------------------------------|--------------------------------------|
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
| Flammability Rating | UL 94 V-0 |
| Safety Standard | UL cUL |

Packaging and Weights

| | |
|---------------------------|---|
| Packaging quantity | 1 |
|---------------------------|---|

Regulatory Compliance/Certifications

Agency**Classification**

CHINA-ROHS

Below maximum concentration value

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

REACH-SVHC

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS

Compliant

UK-ROHS

Compliant

