


EGRZZH4T4VV65DR8V2



30-port sector antenna, 2x 694-862 (R1), 2x 880-960 (R2), 2x 694-960 (R3), 4x 1427-2690 (Y4/Y6), 8x 1695-2180 (B1-B4), 8x 2490-2690 (Y1/Y3/Y5/Y7) & 4x 1695-2690 (Y2&Y8) MHz, 65° HPBW, 8x RET.

- All Internal RET actuators are connected in “Cascaded SRET” configuration

General Specifications

Antenna Type	Sector
Band	Multiband
Grounding Type	RF connector inner conductor and body grounded to reflector and mounting bracket
Performance Note	Outdoor usage Wind loading figures are validated by wind tunnel measurements described in white paper WP-112534-EN
Radome Material	Fiberglass, UV resistant
Reflector Material	Aluminum
RF Connector Interface	4.3-10 Female
RF Connector Location	Bottom
RF Connector Quantity, high band	24
RF Connector Quantity, low band	6
RF Connector Quantity, total	30

Remote Electrical Tilt (RET) Information

RET Hardware	CommRET v1 CommRET v2
RET Interface	8-pin DIN Female 8-pin DIN Male
RET Interface, quantity	1 female 1 male
Input Voltage	10–30 Vdc
Internal RET	High band (5) Low band (3)
Power Consumption, idle state, maximum	2 W
Power Consumption, normal conditions, maximum	9 W
Protocol	3GPP/AISG 2.0 (Single RET)

EGRZZH4T4VV65DR8V2

Dimensions

Width	498 mm 19.606 in
Depth	197 mm 7.756 in
Length	2688 mm 105.827 in
Net Weight, without mounting kit	69.6 kg 153.442 lb


Array Layout

Array	Freq (MHz)	Conns	RET (SRET)	AISG RET UID
R1	694-862	1-2	1	CPxxxxxxxxxxxxxxxxR1
R2	880-960	3-4	2	CPxxxxxxxxxxxxxxxxR2
R3	694-960	5-6	3	CPxxxxxxxxxxxxxxxxR3
B1	1695-2180	7-8	4	CPxxxxxxxxxxxxxxxxB1
B2	1695-2180	9-10		
B3	1695-2180	11-12		
B4	1695-2180	13-14		
Y1	2490-2690	15-16	5	CPxxxxxxxxxxxxxxxxY1
Y3	2490-2690	19-20		
Y5	2490-2690	23-24	6	CPxxxxxxxxxxxxxxxxY5
Y7	2490-2690	27-28		
Y4	1427-2690	21-22	7	CPxxxxxxxxxxxxxxxxY4
Y6	1427-2690	25-26		
Y2	1695-2690	17-18	8	CPxxxxxxxxxxxxxxxxY2
Y8	1695-2690	29-30		

(Sizes of colored boxes are not true depictions of array sizes)

Port Configuration

EGRZZH4T4VV65DR8V2



Electrical Specifications

Impedance	50 ohm
Operating Frequency Band	1427 – 2690 MHz 1695 – 2180 MHz 1695 – 2690 MHz 2490 – 2690 MHz 694 – 862 MHz 694 – 960 MHz 880 – 960 MHz
Polarization	±45°
Total Input Power, maximum	900 W @ 50 °C

Electrical Specifications

	R1	R2	R3	B1-B4	B1-B4	Y1/Y3/Y5/Y7	Y2/Y4/Y6/Y8	Y2/Y4/Y6/Y8	Y4/Y6
Frequency Band, MHz	694–862	880–960	694–960	1695–1880	1920–2180	2490–2690	1695–2180	2490–2690	1427–1518
Gain, dBi	15.2	15.4	16.1	16.2	17.1	17.8	16.9	17.6	14.8
Beamwidth, Horizontal, degrees	68	65	67	69	62	57	62	55	71
Beamwidth, Vertical, degrees	8.6	7.4	8.1	7.4	6.6	5.4	7.1	5.4	9.3
Beam Tilt, degrees	2–14	2–14	2–14	2–12	2–12	2–12	2–12	2–12	2–12
USLS (First Lobe), dB	17	20	19	16	19	17	17	22	18
Front-to-Back Ratio at 180°, dB	32	26	29	32	30	28	34	31	35
Isolation, Cross Polarization, dB	28	28	28	25	25	25	25	25	25

EGRZZH4T4VV65DR8V2

Isolation, Inter-band, dB	28	28	28	25	25	25	25	25	25
VSWR Return loss, dB	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0	1.5 14.0
PIM, 3rd Order, 2 x 20 W, dBc	-150	-150	-150	-150	-150	-150	-150	-150	-150
Input Power per Port at 50°C, maximum, watts	200	200	200	200	200	150	200	200	200

Electrical Specifications, BASTA

Frequency Band, MHz	694–862	880–960	694–960	1695–1880	1920–2180	2490–2690	1695–2180	2490–2690	1427–1518
Gain by all Beam Tilts, average, dBi	14.9	15.1	15.7	15.7	16.7	17.1	16.1	17.2	14.5
Gain by all Beam Tilts Tolerance, dB	±0.4	±0.4	±0.6	±0.5	±0.6	±0.7	±1.1	±0.6	±0.4
Gain by Beam Tilt, average, dBi	2° 14.9 8° 15.0 14° 14.8	2° 15.0 8° 15.3 14° 14.8	2° 15.6 8° 15.8 14° 15.4	2° 15.5 7° 15.7 12° 15.7	2° 16.3 7° 16.8 12° 16.6	2° 16.7 7° 17.4 12° 16.8	2° 15.8 7° 16.2 12° 16.0	2° 16.7 7° 17.4 12° 17.2	2° 14.4 7° 14.6 12° 14.5
Beamwidth, Horizontal Tolerance, degrees	±7.8	±5.9	±6.8	±6.2	±5.1	±6.1	±8.9	±4.4	±7.6
Beamwidth, Vertical Tolerance, degrees	±0.8	±0.4	±1.1	±0.3	±0.4	±0.5	±1	±0.3	±0.5
USLS, beampeak to 20° above beampeak, dB	13	14	16	16	14	16	16	15	16
Front-to-Back Total Power at 180° ± 30°, dB	21	22	22	26	25	21	26	26	26
CPR at Boresight, dB	19	17	18	18	21	19	19	21	17
CPR at Sector, dB	9	12	11	8	6	4	6	3	3

Mechanical Specifications

Mechanical Tilt Range	0°–12°
Wind Loading @ Velocity, frontal	1,070.0 N @ 150 km/h (240.5 lbf @ 150 km/h)
Wind Loading @ Velocity, lateral	375.0 N @ 150 km/h (84.3 lbf @ 150 km/h)
Wind Loading @ Velocity, maximum	1,385.0 N @ 150 km/h (311.4 lbf @ 150 km/h)
Wind Loading @ Velocity, rear	880.0 N @ 150 km/h (197.8 lbf @ 150 km/h)
Wind Speed, maximum	241 km/h (150 mph)

Packaging and Weights

Width, packed	565 mm 22.244 in
Depth, packed	309 mm 12.165 in

EGRZZH4T4VV65DR8V2

Length, packed 2935 mm | 115.551 in

Weight, gross 90.6 kg | 199.739 lb

Regulatory Compliance/Certifications

Agency

CHINA-ROHS

ISO 9001:2015

REACH-SVHC

ROHS

UK-ROHS

Classification

Below maximum concentration value

Designed, manufactured and/or distributed under this quality management system

Compliant as per SVHC revision on www.commscope.com/ProductCompliance

Compliant

Compliant



Included Products

- BSAMNT-4 – Wide Profile Antenna Downtilt Mounting Kit for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor top bracket set and one bottom bracket set.
- BSAMNT-M4 – Middle Downtilt Mounting Kit for Long Antennas for 2.4 - 4.5 in (60 - 115 mm) OD round members. Kit contains one scissor bracket set.

* Footnotes

Performance Note Severe environmental conditions may degrade optimum performance