PS-1-73-EURO



PowerShift® Module, 3 separate 1460 watts circuits per module, 4380 watts total per module, Patent Pending

Reduced capital/operating expenditures

5 A

- Engineering flexibility
- Output to meet European standard

Product Classification

Product Type Module

Product Brand PowerShift®

Product Series V1

Dimensions

Height 41.402 mm | 1.63 in

Width 101.6 mm | 4 in

Depth 351.79 mm | 13.85 in

Compatible Gauge Range 14-6 AWG | 2.5-16 mm²

Electrical Specifications

Input Current, nominal

Input Current Range 0-36 A

Input Voltage Range -42 to -59.5 Vdc

Input Voltage, nominal -54 Vdc

Output Current Range 0-20 A

Output Current, nominal 4 A

Output Voltage Range -48 to -73 Vdc

Output Voltage Regulation0.5 %Output Voltage Ripple100 mVpp

Output Voltage, nominal -60 Vdc

Electrical Safety Standard CE | IEC 60950 | UL | cUL

Electromagnetic Compatibility/Interference (EMC/EMI) EN 55022 Class A

Power Efficiency 95 %

COMMSCOPE®

PS-1-73-EURO

Power Efficiency, nominal 97 %

Programmable RRU Voltage Range -53 to -58 Vdc

Programmable RRU Voltage, nominal 54 Vdc

Total Output Power 1460 W, input voltage dependent

Environmental Specifications

Relative Humidity 5%–95%, non-condensing

Ambient Temperature $65 \,^{\circ}\text{C} \mid 149 \,^{\circ}\text{F}$

Mean Time Between Failures (MTBF) at Temperature 300,000 h @ 25 °C

Packaging and Weights

Packaging quantity

Regulatory Compliance/Certifications

Agency Classification

CE Compliant with the relevant CE product directives

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

