

T350 | RUCKUS T350 Outdoor Access Point



Outdoor 2x2:2 2.4/5GHz Wi-Fi 6 access points with omni and directional antenna

As the market leader in outdoor Wi-Fi deployments, RUCKUS knows that one AP solution cannot meet every possible challenge of varied and complex outdoor requirements. The RUCKUS T350 Wi-Fi 6 series is designed with more variety than any other outdoor AP in the market today. Perfect for high-density outdoor public venues such as airports, convention centers, plazas, malls, smart cities, and other dense urban environments.

Available with either internal omni-directional antennas or internal high-gain directional antenna models, the T350 Series uses patented RUCKUS antenna optimization and interference mitigation technologies to improve throughput, connection reliability, and deliver industry-leading Wi-Fi 6 performance to every connected client.

At the same time, the T350 Series is designed for fast, simple installation with an ultra-lightweight, low profile, IP-67 rated enclosure that can stand up to the most challenging outdoor environments.

Product Classification

Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Type	Outdoor access point
Product Brand	RUCKUS®

General Specifications

Antenna Patterns, per band	64
Antenna Gain	Omni: Up to 3 dBi
BeamFlex	Yes
ChannelFly	Yes
Controller Support	RUCKUS Cloud™ RUCKUS SmartZone RUCKUS Unleashed™ RUCKUS ZoneDirector Standalone
Ethernet Ports	1 x 1 GbE RJ45 PoE In - 802.3 at Class 4
Fiber Interface	No
IoT Support	IoT Onboard (only d series)
PD-MRC	Yes
PHY Rate at 2.4 GHz, maximum	574 Mb/s
PHY Rate at 5 GHz, maximum	1200 Mb/s
Radio Chains and Streams	2x2:2
Rx Sensitivity at 2.4 GHz	-94 dBm

T350 | RUCKUS T350 Outdoor Access Point

Rx Sensitivity at 5 GHz	-95 dBm
SmartMesh	Yes
USB	USB 2.0 Type A
Venue Type	Education Hospitality Public Venue
Venue Sub-Type	Quad/Blacktop/Outdoor Spaces
Wi-Fi Interface Standard	IEEE 802.11a/b/g/n/ac/ax
Wi-Fi Interface Standard at 2.4 GHz	802.11ax
Wi-Fi Interface Standard at 5 GHz	802.11ax