# 760087973 | RFE-MOD-012-5K-MPO-LC02-KSL



Product Classification

#### ReadyPATCH® Multimode OM4 Keyed Module, 12 LC ports, slate

• Part of the Uniprise® ReadyPATCH® Pre-terminated Fiber line

Regional Availability	North America
Portfolio	CommScope®
Product Type	Fiber module
Product Brand	LazrSPEED®   ReadyPATCH®
General Specifications	
Functionality	Breakout
Adapters, quantity, front	б
Adapters, quantity, rear	1
Color, front	Slate
Color, rear	Gray
Interface, front	LC/UPC
Interface Feature, front	Keyed
Interface, rear	MPO
Interface Feature, rear	Male
Polarity	Method B
Shuttered	Yes
Total Fibers, quantity	12
Total Ports, quantity, front	12
Dimensions	
Height	27.94 mm   1.1 in
Width	129.54 mm   5.1 in
Depth	127 mm   5 in
Optical Specifications	

Fiber Mode

Multimode

Page 1 of 3

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 3, 2024



# 760087973 | RFE-MOD-012-5K-MPO-LC02-KSL

550

Fiber Type	OM4, LazrSPEED®
Insertion Loss Change, mating	0.3 dB
Insertion Loss Change, temperature	0.3 dB
Insertion Loss, maximum	0.9 dB

# Environmental Specifications

Safety Standard	UL
-----------------	----

#### Packaging and Weights

Packaging quantity

### Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

1



#### Included Products

460117468

 LazrSPEED® LC Duplex Hybrid Keyed Adapter, Slate

# \* Footnotes

Insertion Loss Change, mating	Maximum insertion loss change after 500 matings
Insertion Loss Change, temperature	Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 3, 2024



#### LazrSPEED® LC Duplex Hybrid Keyed Adapter, Slate

#### Product Classification

Regional Availability	Asia   Australia/New Zealand   EMEA   Latin America   North America	
Portfolio	CommScope®	
Product Type	Fiber adapter	
Product Brand	LazrSPEED®	

# General Specifications

Body Style	Duplex
Color	Slate
Interface	LC/UPC
Interface Feature	Keyed
Mounting	No flange
Shuttered	No
Total Ports, quantity	2
Transmission Standards	TIA/EIA-568-B.3   TIA/EIA-604 FOCIS-3

#### Material Specifications

Alignment Sleeve Material Zirconia

### **Optical Specifications**

Fiber Mode Multimode | Singlemode

1

# Packaging and Weights

Packaging quantity

#### Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

Page 3 of 3

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 4, 2024

