# 760167866 | RP-MOD-012-LS-MPO-LC02



### ReadyPATCH® Multimode OM4 Standard Module, 12 LC ports

#### **Product Classification**

Regional AvailabilityNorth AmericaPortfolioCommScope®Product TypeFiber module

Product Brand LazrSPEED® | ReadyPATCH®

## General Specifications

**Functionality** Breakout

Adapters, quantity, front 6
Adapters, quantity, rear 1

Color, frontAquaColor, rearGray

Data Module TypeStandardInterface, frontLC/UPCInterface, rearMPO

Interface Feature, rear Male | Reduced footprint

**Polarity** Method B

ShutteredYesTotal Fibers, quantity12Total Ports, quantity, front12

#### Dimensions

 Height
 27.94 mm | 1.1 in

 Width
 129.54 mm | 5.1 in

 Depth
 127 mm | 5 in

Optical Specifications

Fiber Mode Multimode

Page 1 of 2

# 760167866 | RP-MOD-012-LS-MPO-LC02

**Fiber Type** OM4, LazrSPEED® 550

Insertion Loss Change, mating0.3 dBInsertion Loss Change, temperature0.3 dBInsertion Loss, maximum0.9 dB

## **Environmental Specifications**

Safety Standard UL

Packaging and Weights

Packaging quantity

## Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



### \* Footnotes

**Insertion Loss Change, mating**Maximum insertion loss change after 500 matings

Insertion Loss Change, temperature Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)

