

NG4access® Module VAM, Splitter, 1x4, symmetrical split, singlemode, LC /APC, front, right, 4 circuits

- VAMs help enhance optical transport systems by providing flexible, easy to incorporate optical components into the network
- VAMs increase fiber capacity and help troubleshooting or distributing signals to multiple subscribers
- *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

Product Classification

PortfolioCommScope®Product TypeSplitter moduleProduct BrandNG4access®Product SeriesFACT NG4Government RequirementsBuild America Buy America (BABA) compliant*General SpecificationsPlug-and-play moduleFunctionalitySplitting
Product BrandNG4access®Product SeriesFACT NG4Government RequirementsBuild America Buy America (BABA) compliant*General SpecificationsPlug-and-play module
Product SeriesFACT NG4Government RequirementsBuild America Buy America (BABA) compliant*General SpecificationsPlug-and-play module
Government RequirementsBuild America Buy America (BABA) compliant*General SpecificationsPlug-and-play module
General Specifications Plug-and-play module
Device Type Plug-and-play module
Functionality Splitting
Technology TypePlanar lightwave circuit (PLC)
Access Front
Application For use with NG4 access frames
Distribution Type1 x 4 splitter
Interface, front LC/APC
Interface, Input LC/APC
Interface, Output LC/APC
Location of ManufacturingWaived per BABA waiver for BEAD Program
Split Ratio Symmetrical
Splitter, quantity 4

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 1, 2024



NG4-VSMRF44

Tray Orientation	Right orientation
Dimensions	
Height	13.21 mm 0.52 in
Width	159.77 mm 6.29 in
Depth	130.3 mm 5.13 in
Optical Specifications	
Directivity, minimum	55 dB

Directivity, minimum	55 dB
Performance Grade	Grade O (PLC, low loss)
Polarization Dependent Loss, maximum	0.15 dB
Uniformity, maximum	0.85 dB
Wavelength Range	1260-1625 nm
Insertion Loss, Splitter, maximum	7.5 dB
Return Loss, Connector, minimum	55 dB

Packaging and Weights

Packaging quantity

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

1



Page 2 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 1, 2024

