

NG4access® Module VAM, Splitter, 1x2, symmetrical split, singlemode, LC /APC, front, right, 8 circuits

- VAMs help enhance optical transport systems by providing flexible, easy to incorporate optical components into the network
- VAMs increase fiber capacity and help troubleshooting or distributing signals to multiple subscribers
- *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

Product Classification

Regional Availability	Asia Australia/New Zealand China EMEA India Latin America North America				
Portfolio	CommScope®				
Product Type	Splitter module				
Product Brand	NG4access®				
Product Series	FACT NG4				
Government Requirements	Build America Buy America (BABA) compliant*				
General Specifications					
Device Type	Plug-and-play module				
Functionality	Splitting				
Technology Type	Planar lightwave circuit (PLC)				
Access	Front				
Application	For use with NG4 access frames				
Distribution Type	1 x 2 splitter				
Interface, front	LC/APC				
Interface, Input	LC/APC				
Interface, Output	LC/APC				
Location of Manufacturing	Waived per BABA waiver for BEAD Program				
Split Ratio	Symmetrical				
Splitter, quantity	8				

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 1, 2024



NG4-VSMRF8C

Tray Orientation	Right orientation				
Dimensions					
Height	13.21 mm 0.52 in				
Width	159.77 mm 6.29 in				
Depth	130.3 mm 5.13 in				
Optical Specifications					
Directivity, minimum	55 dB				
Performance Grade	Grade O (PLC, low loss)				
Polarization Dependent Loss, maximum	0.15 dB				
Uniformity, maximum	0.85 dB				
Wavelength Range	1260–1625 nm				

			 · .	

Insertion Loss, Splitter, maximum

Return Loss, Connector, minimum

Packaging and Weights Packaging quantity

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

4.2 dB

55 dB

1



Page 2 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: October 1, 2024

