

# C400-NMNF-M3

---

CNT-400 CNT® Jumper with interface types N Male and N Female, 0.3



## Product Classification

|                       |                        |
|-----------------------|------------------------|
| <b>Product Type</b>   | Braided cable assembly |
| <b>Product Brand</b>  | CNT®                   |
| <b>Product Series</b> | CNT-400                |

## General Specifications

|   |                  |
|---|------------------|
| <b>Attachment, Connector A</b>            | Field attachment |
| <b>Attachment, Connector B</b>            | Field attachment |
| <b>Body Style, Connector A</b>            | Straight         |
| <b>Body Style, Connector B</b>            | Straight         |
| <b>Cable Family</b>                       | CNT-400          |
| <b>Interface, Connector A</b>             | N Male           |
| <b>Interface, Connector B</b>             | N Female         |
| <b>Specification Sheet Revision Level</b> | A                |

## Dimensions

|                     |                  |
|---------------------|------------------|
| <b>Length</b>       | 0.3 m   0.984 ft |
| <b>Nominal Size</b> | 0.400 in         |

## VSWR/Return Loss

| Frequency Band | VSWR  | Return Loss (dB) |
|----------------|-------|------------------|
| 700–3000 MHz   | 1.288 | 18               |

## Jumper Assembly Sample Label

# C400-NMNF-M3



## Regulatory Compliance/Certifications

| Agency        | Classification   |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |

## Included Products

|             |   |
|-------------|---|
| 400APNM-C   | - Type N Male for CNT-400 braided cable   |
| 400BPNM-C   | - Type N Male for CNT-400 braided cable   |
| 400PNF-C    | - Type N Female for CNT-400 braided cable   |
| CNT-400     | - CNT-400, CNT® 50 Ohm Braided Coaxial Cable, variable, black PE jacket   |
| CNT-400-SFR | - CNT-400-SFR, C CNT® 50 Ohm Braided Coaxial Cable, black non-halogenated, fire retardant polyolefin jacket, B2ca S1a d0 a1 Compliant |
| CNT-400-W   | - CNT-400-W, CNT® 50 Ohm Braided Coaxial Cable, variable, white PE jacket   |