# S-4-UW-H-NI6



Ultra Wideband Four-way Low PIM Reactive High Power Splitter, 555–6000 MHz (Additional mounting bracket PN:42396A-17 sold separately)

#### **Product Classification**

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

**Product Type** Power splitter

General Specifications

**Device Type** Splitter

**Application** Indoor/Outdoor

Color White
Inner Contact Plating Silver
Interface N Female

Outer Contact Plating Trimetal

**Dimensions** 

 Height
 43 mm | 1.693 in

 Width
 61 mm | 2.402 in

 Length
 249 mm | 9.803 in

**Electrical Specifications** 

**3rd Order IMD** -163 dBc

**3rd Order IMD Test Method** Two +43 dBm carriers

Insertion Loss at Frequency Band 0.3 dB @ 555-2700 MHz | 0.55 dB @ 2700-3800 MHz | 0.75 dB @ 3800-4900

MHz | 1.4 dB @ 4900-6000 MHz

Average Power, maximum 300 W

**Impedance** 50 ohm

**Operating Frequency Band** 555 – 6000 MHz

Peak Power, maximum3 kWPower Rating, Splitting300 WReflected Power, maximum300 W

Page 1 of 2



# S-4-UW-H-NI6

Split Loss 6 dB

**VSWR at Frequency Band** 1.25 @ 555-2700 MHz | 1.25:1 @ 2700-3800 MHz | 1.3:1 @ 3800-6000 MHz

Mechanical Specifications

**Coupling Nut Proof Torque** 4.5 N-m | 39.828 in lb

### **Environmental Specifications**

**Operating Temperature**  $-35 \,^{\circ}\text{C} \text{ to } +85 \,^{\circ}\text{C} \, (-31 \,^{\circ}\text{F to } +185 \,^{\circ}\text{F})$ 

**Relative Humidity** Up to 100%

Corrosion Test Method IEC 60068-2-11, 30 days
Ingress Protection Test Method IEC 60529:2001, IP67

### Packaging and Weights

 Height, packed
 55 mm | 2.165 in

 Width, packed
 77 mm | 3.031 in

 Length, packed
 315 mm | 12.402 in

 Weight, gross
 0.47 kg | 1.036 lb

 Weight, net
 0.39 kg | 0.86 lb

## Regulatory Compliance/Certifications

#### Agency Classification

CHINA-ROHS Above maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted

