760249957 | SFC-12MX-8LL-RN-YL



Qwik-Fuse MPO Connector, PINNED, Singlemode-APC, Yellow, Bare Ribbon cable, Male, High Performance, Single pack

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

Portfolio CommScope®

Product Type Fiber connector

Product Brand Qwik | TeraSPEED®

Product Series Qwik-Fuse

General Specifications

Color, boot Yellow
Black

Ferrule Geometry Factory polished

Interface MPO/APC Male

Interface Feature Field Installable | Fusion splice | Pinned

Total Fiber Count 12

Dimensions

Length 41.6 mm | 1.638 in

Material Specifications

Ferrule Material Polymer

Mechanical Specifications

Cable Retention Strength, maximum $11.24 \text{ lb} @ 0 ^{\circ}$

Optical Specifications

Fiber Mode Singlemode

Fiber Type OS2

Insertion Loss Change, mating 0.3 dB

Optical Components Standard ANSI/TIA-568. 3-D

Page 1 of 2

760249957 | SFC-12MX-8LL-RN-YL

Insertion Loss Change, temperature0.3 dBInsertion Loss, maximum0.35 dBInsertion Loss, typical0.1 dBReturn Loss, minimum60 dB

Environmental Specifications

Operating Temperature $-40 \,^{\circ}\text{C}$ to $+75 \,^{\circ}\text{C}$ ($-40 \,^{\circ}\text{F}$ to $+167 \,^{\circ}\text{F}$)

Packaging and Weights

Packaging quantity

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant



* Footnotes

Insertion Loss Change, matingTIA-568: Maximum insertion loss change after 500 matings

Insertion Loss Change, temperature Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F)

