C

includes hardware

Product Classification

| Product Type | Hanger kit |
|------------------------------|--|
| Product Brand | KwikClamp™ |
| Ordering Note | CommScope® standard product in Europe, the Middle East, and Africa Minimum order quantity (MOQ) is 1 box |
| General Specifications | |
| Cables per Hanger | 1 |
| Color | Black |
| Hanger Type | KwikClamp™ hanger |
| Mounting | 3–25 mm angle iron 3–25 mm flat plate Round Member 8- 25 mm |
| Dimensions | |
| Maximum Stack Height | 1 |
| Height | 111 mm 4.37 in |
| Width | 31 mm 1.22 in |
| Length | 42 mm 1.654 in |
| Compatible Diameter, maximum | 14 mm 0.551 in |
| Compatible Diameter, minimum | 13 mm 0.512 in |
| Nominal Size | 1/2 in |
| Hanger Spacing, maximum | 1.83 m 6.004 ft |
| Electrical Specifications | |
| Return Loss Effect, maximum | 0.1 dB |
| DTF Effect, maximum | 0.1 dB |
| | |

KwikClamp[™] Hanger for 1/2 in superflexible coaxial cable, single stack;

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: June 13, 2024



Page 1 of 2

F4-CLAMP-1B

Material Specifications

| Material Type | Engineered plastic Stainless steel |
|---------------------------|--------------------------------------|
| Mechanical Specifications | |
| Vibration Survival | ≥4 hours at resonant frequency |

Environmental Specifications

| Operating Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |
|---|--|
| Corrosion Resistance, minimum with no degredation | ≥500 hours in salt spray chamber |
| Environmental Strength Capability | Five times cable weight |
| UV Resistance, minimum with no degradation | \geq 100 hours exposure in accelerated UV life chamber |

Packaging and Weights

| Height, packed | 15.5 cm 6.102 in |
|--------------------|---------------------|
| Width, packed | 30.5 cm 12.008 in |
| Length, packed | 35.5 cm 13.976 in |
| Included | Hardware |
| Packaging quantity | 90 |
| Weight, gross | 7.9 kg 17.416 lb |

Regulatory Compliance/Certifications

| Agency | Classification |
|------------|---|
| CHINA-ROHS | Below maximum concentration value |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |
| | |



* Footnotes

Maximum Stack Height Fiber, Hybrid, Power

Page 2 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: June 13, 2024

